

Technical specifications

Type		211001	UP 116/01	221001	UP 116/11	210F01	UP 116/21	220F01	UP 116/31
Application program									
Enclosure data									
For installation in flush-mounting switch and socket boxes with Ø = 60 mm and depth = 60 mm			✓	✓	✓	✓	✓		
Dimensions									
• Height	mm	71	71	71	71	71	71		
• Width	mm	71	71	71	71	71	71		
• Depth	mm	32	32	32	32	32	32		
Mounting type									
Claw fixing			✓	✓	✓	✓	✓		
Screw fixing			✓	✓	✓	✓	✓		
Display/control elements									
LED per pushbutton pair for status indication or configurable as orientation light			1	1	1	1	1		
Mounting of rockers from the DELTA product ranges			✓	✓	✓	✓	✓		
Rocker button, intermediate position (pushbutton with 2 operating points)			1	2	--	--	--		
Rocker button, pushbutton position (pushbutton with 1 operating point)			--	--	1	2	2		
Bus connection									
Integrated bus coupling unit			✓	✓	✓	✓	✓		
General functions									
Maximum number of group addresses			4	8	3	4	4		
Maximum number of assignments			4	8	3	5	5		
Input functions									
Switching									
Switching ON/OFF			✓	✓	✓	✓	✓		
Switching over			✓	✓	✓	✓	✓		
Dimming									
Dimming with stop telegram (4-bit) Short button press, ON/OFF Long button press, brighter/darker			✓	✓	--	--	✓		
Dimming with cyclic transmission (4-bit) Short button press, ON/OFF Long button press, brighter/darker			✓	✓	--	--	✓		
Shutter/blind									
Shutter/blind control Short button press, slat OPEN/CLOSED or STOP Long button press, UP/DOWN			✓	✓	--	--	✓		
Scene									
Store and call up scene, 1-bit in conjunction with scene module			1	2	--	--	--		
Short or long button press (store/call up scene), configurable			✓	✓	--	--	--		
Status									
Display of any status objects (1-bit)			✓	--	--	--	--		
Display of pushbutton objects			✓	--	✓	✓	✓		